



ULC-T Line Card

The universal transmit line card, ULC-T, features DVB-S2 up to 54MHz or DVB-S2X up to 125MHz carrier bandwidth with Adaptive Coding and Modulation (ACM) on the outbound channel. In conjunction with a multi-channel demodulator line card (e.g. ULC-R), the ULC-T is ideally suited for broadband applications such as Internet and VPN access to enterprise networks, along with real-time VoIP and videoconferencing on both the ST Engineering iDirect Evolution® and Velocity® platforms.

Network Configuration

Network Technology	DVB-S2 , DVB-S2X
Modem	One Modulator (Transmit one downstream carrier)
Modulation	DVB-S2: QPSK, 8PSK, 16APSK, 32APSK DVB-S2X: QPSK, 8PSK, 16APSK, 32APSK, 64APSK, 128APSK, 256APSK
FEC	DVB-S2: LDPC 1/4 - 8/9 DVB-S2X: LDPC 9/20 - 3/4
Symbol Rate	DVB-S2: Up to 45 Msps DVB-S2X: Up to 119 Msps*

Interoperability

Compatible with Series 15100 Universal Hub (5IF/20 Slot)
DVB-S2 requires Evolution 3.4 / Velocity 1.1 software or above
DVB-S2X requires Evolution 4.1 or above

All specifications are software dependent.

* Specifications are modem dependent.

EVOLUTION

VELOCITY

powered by

Newtec 

Interfaces

SatCom Interfaces

TxIF: Type-F, 950–2000 MHz, +5/-35 dBm power

Data Interfaces

GigE LAN A: Data & Control; GigE LAN B: Data & Control. Link Aggregation.
Console: RS232 over RJ-45

Timing Interface

Locked to customer supplied PPS/10 MHz through backplane

Other Features

Linear pre-distortion

Mechanical & Environmental

Redundancy	Software controlled, hot-swappable, and auto-failover
Weight	0.83 kg (1.48 lbs)
Operating Temperature	0° to +45°C (+32° to +113°F)
Humidity	0–95% non condensing
Input Voltage	24V; 65W (max)